

Order form / quote

Internal sliding S shutter

Customer number

Name

Address

Agency

Date

☐ Quote

Work ref.

☐ Order

Order number

Reference	Units	Colour	Opening dimensions		Slats models		Version	Central divider leaf ¹		Locking position ² (C)	Lock installed on leaf ³		Bottom guide type					Guide length (mm) ⁴
			Height (mm)	Width (mm)	Fixed D-5	Mobile D-7		Vertical Blinds	Graphic Layout		Leaf	Position A/B	Surface	Channel	Pivot	Surface with wall fixings	Pivot with wall fixings	

Tipo de guía inferior

Pocket door with bottom guide installed inside the chamber

External

Interior

External

Interior

External

Interior

Surface

Channel

Pivot

56

26 30

101

26 45 30

146

26 45 45 30

Dimensions in mm.

Pocket door with bottom guide installed outside the chamber

External

Interior

External

Interior

Surface with wall fixings

Pivot with wall fixings

Maximum number of guides 3

56

26 30

101

26 45 30

146

26 45 45 30

Height luz

78

44

Dimensions in mm.

Features

Maximum and minimum manufacturing dimensions

Height mm

Min - Max

Width mm

Min - Max

1i o 1d400 - 3.000200 - 2.000

1i + 1d400 - 3.000400 - 4.000

2i o 2d400 - 3.000345 - 3.945

Maximum and minimum manufacturing dimensions

Height mm

Min - Max

Width mm

Min - Max

2i + 2d400 - 3.000690 - 7.890

3i o 3d400 - 3.000490 - 5.890

3i + 3d400 - 3.000980 - 11.780

*All leaves are of the same dimensions.

¹ If height of leaf >1800 mm it will be manufactured with a horizontal crosspiece.
If width of leaf >1000 mm it will be manufactured with a vertical crosspiece.

² By default, the double action closure (C) will always be installed inside, indicate if it is installed outside.

³ For the side lock, note that the span width does not include the width of the tube on which the leaf closes. Tube not included.

⁴ By default the guide length is twice the span width, otherwise indicate the guide length.

Administration signature

Print

Save

Delete

Send

Version (viewed from the inside)

Observations

