

Assembly instructions

Duplex Bioclimatic Pergola P-150

4 columns




Table of Contents

We do not provide the screws for fixing-anchoring to the wall and/or foundations. The fitter must choose the adequate rod/screw/plug/nut/washer system for fixing and flushing to the foundations and/or wall based on the nature of these surfaces. In any case, the screws must be in stainless steel.

- 1. Installation 4**
 - 1.1 Installing fixing base columns surface..... 4*
 - 1.2 Assembling the opening beam with the A and B columns and closing beam with the C and D columns..... 7*
 - 1.3 Assembling the left beam with A and C columns..... 9*
 - 1.4 Assembling the central beam 10*
 - 1.5 Assembling the right beam with B and D columns 11*
 - 1.6 Joining the surface manifolds in the opening and closing beam 12*
 - 1.7 Installing the rubber 14*
 - 1.8 Installing “U” draining profile, opening, closing, central and laterals 15*
 - 1.9 Drainage channel closed column 16*
 - 1.10 Installing the slat, transmission plate and motor tandem axle 17*
 - 1.11 Motor installation 22*

- 2. Electrical connections 23**

The connection of the electrical installation must be done adhering to the current regulations for low voltage (REBT).

 - 2.1 Teleco documentation..... 23*
 - 2.2 Somfy documentation..... 23*
 - 2.3 Installation of automatic devices on beams..... 23*
 - 2.4 Perimeter LED installation..... 24*

- 3. Installing column cup 25**


- 4. Maintenance 26**

Before assembling, please read the maximum tightening torque for each type of screw, as indicated in this section.


- Annex I Removal of slats 27*
- Annex II Disassembly and disposal of packaging and product components at the end of the product's service life . 28*
- Annex III Warranty certificate 32*
- Bioclimatic Pergola installation check sheet..... 34*

1. Installation

1.1 Installing fixing base columns surface



Fixing surface 304 stainless steel column base
Code 050214



Measure the foundation in order to make sure that the levelling is correct.

Install the base fixings using M-12 screws (not included), with a quality of at least AISI 304 (stainless steel), leaving all bases properly levelled.


Once the column bases are installed in place, measure the diagonal lines to ensure both distances are equal.



The correct installation of the column bases is critical for the pergola optimum operation.

! Attention

Recommended installation is against a wall with reinforced concrete floor at least 150 mm thickness (or surface of equivalent strength) by means of 12 mm stainless steel fittings (not included).


Leave a 100 mm space above the beam so the slats can turn.





! Important


Make sure you know which end of the left and right beam corresponds to the opening and closing. In the figure, we show the distance from the first pre-drilled hole in the opening and in the closing.



Install the motor on the central beam using the ULS ISO 7380 A2 M6x16 screws, inserting them in the pre-drilled threads created for this purpose on the closing area of the central beam.

! Important


If the pergola is equipped with LED lines, you must pass the LED connector cables through the corresponding slat hole and take them to the closing area to pull the out through the hole pre-drilled in the column for this purpose, as well as the motor cable, which should be put through the cable gland.




1.2 Assembling the opening beam with the A and B columns and the closing beam with the C and D columns

Join the A and B columns to the ends of the **opening** beam.
 Join the C and D columns to the ends of the **closing** beam.
 Use the brackets and screws provided (see image).

Fasten the screws 1, 2 and 3 on the inner part of the column, use the washers provided.



Keeping the opening and closing beams together with the columns, fasten them to the columns bases on the floor surface using the ULS (ISO 7380) A2 M6x16 mm screws. Proceed as shown in the image.





1.3 Assembling the left beam with A and C columns

Join the **left** beam, to the A and C columns.

Follow the screwing sequence.

Use the brackets and screws provided.





1.4 Assembling the central beam

When mounting the central beam, you should pass the LED connectors and motor connection cable through to the closing beam using a purposely pre-drilled hole. Once inserted into the closing beam, take them towards the required column to complete the connection.

Mount the **central** beam between the opening and closing beams.

Match the holes in the top plates of the central beam with the top rivet nuts on the opening and closing beams. Simultaneously match the holes in the S duplex bottom plate supporting the opening and closing beam.

Tighten all the plates using the ULS (DIN 7380) A2 M6x16 screws provided.



1.5 Assembling the right beam with B and D columns


Join the **right** beam, to the B and D columns.

Follow the screwing sequence.


Use the brackets and screws provided.

Important

Tighten the screws with the torque indicated in the maintenance section.




1.6 Joining the surface manifolds in the opening and closing beam




Apply the provided sealant between the contact sides of the **opening** and **closing** beams and their corresponding surface manifolds.

Clip the **opening** and **closing** manifolds (same profile, just in an inverted position). You will possibly need to use clamps or wooden blocks to help you with the clipping.




! Important

Do not bypass this step, it is very important to seal the manifold joint properly (sealant provided).




! Important


Create a groove at the ends of the opening manifold, before proceeding with the installation, (use a hammer and a flat screwdriver).




1.7 Installing the rubber




Installing rubber on the clippable opening gutter.




Installing rubber on the last slat.
Installed in the opposite way to the rest of lasts.
The clippable closing gutter does not have rubber.




Installing rubber on the slats (150 slat step).



Installing rubber on the slats (150 to 160 slat step).




1.8 Installing "U" draining profile, opening, closing, central and laterals





Install the "U" draining profile on the **left** and **right** beams. To do it, insert the profile end through the draining hole pre-drilled on columns A and B and leave it flush with the beam and columns C and D.

Mount the U-shaped grooves on the central beam, flush with the opening and closing beams, just as you did with the U-shaped drain grooves 62x65x2,5 along the opening beam, inserting the A and B column ends into the closing beam, flush with the C and D columns.



Check that all the "U" profile holes match the M6 pre-drilled ones on the beam.

If all of them match, apply the sealant between the "U" profile and the beam after screwing the profiles with the ULS (ISO 7380) A2x16 screws.





Use the sealant provided to seal the "U" profiles to the beams and the joints that could suffer water leaks.

1.9 Drainage channel closed column

When the closed column is channelled through the foundations, start by installing the column fixings. Calculate the length of the 75 mm PVC drainage pipe, depending on the height of the pergola and the height at which the collecting tray will be installed.

Please note that the tray must be installed at a minimum distance of 250 mm from the top of the column; insert the drain pipe through the top of the column and connect it to the bottom drain of the foundations.


Then insert the collecting tray (by tilting it) and position it on the tube, joining the assembly with the joint adapter.




Finally, apply the sealant (included) all around the perimeter of the collecting tray and the adapter, as shown in the picture (sealant in red), and insert the universal leaf guard into the adapter.

1.10 Installing the slat, transmission plate and motor tandem axle

Before installation of the slats, place the 16,6x11 mm anti-friction caps.



To install the slats without LED you will have a set of O-210 pivot-type caps, integrated by a 16,4x25 mm plastic cap and a retractable stainless steel axle.



The slats with LED come already pre-installed on one side with a hollow axle. The LED connector comes through this axle and it has a protection spring. The O-210 retractable axle needs to be installed on the other end.

! Important


Pay attention when installing the slats so there are no errors or confusion in their placement, opening, closing, LED slats, etc. If it was necessary to remove any of the slats, follow the steps described in annex A.

! Important

The central beam transmission plates must be installed simultaneously with the mounting of the slats in duplex pergola panels (install 2 or 3 slats, then install the plates).

Start installing the slats from the **closing** beam and from the top part of the pergola.


Insert the slat axle into the left beam, lower the right side at the same time you insert the retractable axle into the end cap and insert it into the anti-friction cap of the right beam, so the slat is finally in place.




! Important

The central beam transmission plates must be installed simultaneously with the mounting of the slats in duplex pergola panels (install 2 or 3 slats, then install the plates).

To mount the motor there is a tandem axle holding the two central transmission plates. These have two pre-drilled holes and must be installed towards the closing area nearest to the motor area, 5th or 6th slat.



If you prefer, the **left** and **right** beam plates can be mounted after all the slats have been inserted.





Join the plates to the end caps with their corresponding ULS (ISO 7380) A2 M6x16 screws, 6,3 mm rimmed plastic caps and M6 DIN 985 nut.

! Important

When installing the plate in the slats, do not tighten too much the screw nuts, so they are set without tightening. Thus the plate can perform manually the opening and closing movements with no friction whatsoever.


When reaching a hole for LED slats, connect the connector and insert it into the beam (as shown in the images below).

As for the other slats, the installation is the same, inserting the connector axle into the beam with the LED installation and the retractable axle into the other beam.



When proceeding to mount the 5th or 6th slat, you will reach the area with the pre-drilled holes in the transmission plates, intended to install the **complete tandem axle set** with code: 050307.

The transmission plates have some pre-drilled holes to mount the driving tandem axle, which should be placed near the **closing** area.





1.11 Motor installation

You should already have the motor on the central beam, unless otherwise specified in the manufacturing order.


Steps to join the motor to the transmission plate tandem axle.

- 1 Move the tandem axle, together with the transmission plates and mounted slats, until the tandem axle carrying mount matches the motor rod.
- 2 Fasten it by inserting the pin and cotter pins or screw provided.



There could be variations in the mounts for the motor and tandem axes provided, but all the pre-drilled holes made in the pergola, as well as the screws and pins provided, will be adequate for each case.

Continue mounting the slats and transmission plates until completing the last slat, the opening one.



2. Electrical connections

! Attention

The reception of the operators can be reduced or cancelled by the emission of frequencies that are issued in the same range as our automatisms.

The connection of the electrical installation must be in compliance with the rules and regulations of each country (Low voltage electrotechnical regulation). The perimeter cabling for the electrical and sound installations will be passed through the beam and column spaces.

The cable of the motor will go through the "U" profile towards the end where the electric connection will be performed, making a loop at the motor outlet and passing it under the support, so it cannot be pinched by the transmission plate when the assembly moves.

Complete the electric connections of the pergola according to the instructions and considering that both the motor and the LEDs run with a 24V voltage. For this reason, it is necessary to use the power source and switchboard provided for the pergola operation.

For greater safety, it is necessary to ground the pergola.

! Attention

It is recommended to place the electrical components on a column where the drainage of the pergola is not located. If this is not possible, seal all joints of the drainage parts of the column where electrical components are placed.

2.1 Teleco Documentation



Scan the QR code with your mobile device or click to access Teleco Documentation

Teleco Automation System Documentation

1. Programming the automation systems
2. Quick guides
3. Motor configuration
4. Using the transmitter
5. Sensors
6. Supplier documentation

2.2 Somfy Documentation



Scan the QR code with your mobile device or click to access Somfy Documentation


Somfy Automation System Documentation

1. Electrical connections
 - 1.2 Wiring diagram
 - 1.2.1 Wiring
 - 1.2.2 RTS programming (factory set)
 - 1.2.3 Electrical connection of the Bos io Louver Control Centre

2.3 Installation of automatic devices on beams


When Teleco automatic devices are chosen, the control units are placed inside the closing beam on the side where the motor is installed.

For this purpose, a rubber gasket is fitted and the cover is fixed by means of 4 ULS ISO 7380 screws + A2 washer M6X16 as shown in the reference picture.






2.4 Perimeter LED installation

If the pergola is fitted with perimeter LEDs, an aluminium profile with an LED strip will be installed in the gutters of the pergola.






Fit the perimeter LED corner piece shown in the picture on the right to the **corners of the pergola with a column**.

The perimeter LED profiles should be 9 mm from the column.



Fit the perimeter LED corner piece shown in the picture on the right to the **corners of the pergola with a mitre**.

The perimeter LED profiles should be 19 mm from the column.



4. Maintenance

Before assembling, please read the maximum tightening torque for each type of screw, as indicated in this section.

For best use and extended durability of your pergola, it is recommended to carry out regular maintenance and services at least once a year, or even more often depending on the wind fatigue at the installation site.

To prevent corrosion, it is recommended to periodically clean gutters and sections with neutral soap. The minimum frequency is once a year, and must be increased for cloths exposed to aggressive environments (marine, industrial, airborne dust particles, etc.). It is important to rinse thoroughly with water, after using detergents, to avoid the formation of salts on the surface of the sections.

When properly done, this periodical cleaning removes from the surface of the cloth the exogenous agents that can attack the coating and aluminium, extending the life of the sections and their aesthetic performance.

Inspection of seals, revision of the electrical installation, as well as a review of the tightening of screws according to the tightening torques (standard metric thread) set forth in the attached table.

SCREWS HARDNESS CATEGORY 70



THREAD	µges.	MA TIGHTENING TORQUE (Nm)
M5	0,2	5,7
M6	0,2	10
M8	0,2	24

Annex I

Removing slats

If for any reason it was necessary to remove any slat from the P-150 bioclimatic pergola, the steps below must be followed:

- Unscrew the end cap of the slats to be removed and turn the slat so it is possible to see its interior shaft.
- Insert a screwdriver into the groove supporting the end of the slat shaft and press in to remove the shaft from the beam cap. While pressing the shaft, pull the slat upwards to remove it from the beam.

**! Important**

If the slat being replaced is the closing or the opening one, it will not be possible to unscrew the end caps because it cannot be pulled, so you will need to drill a hole at the top of the slat, at the shaft level, using a bit with a diameter large enough to insert the screwdriver and proceed as described previously.

If it were necessary to reuse these slats, you would need to seal the hole with a 25 mm cap.

Disassembly and disposal of the packaging and components of the product at the end of its useful life

Disposal of packaging

Important

The packaging must be recycled by the authorised professional who installed the product.

We advise you to recycle the product packaging responsibly:

- Please dispose of this waste in accordance with the current regulations:
 - Directive 94/62/EC on packaging and packaging waste.
 - Spanish Law 11/1997 of April 24th on packaging and packaging waste.
- Please sort the waste by separating each and every one of the various materials, to facilitate effective disposal of the packaging.
- Do not dispose of packaging materials together with other types of waste. Take them to a packaging materials collection point designated by the local authorities.
- In order to minimise the environmental impact of packaging and packaging waste, it is necessary to define the composition and nature of the packaging of our products to recommend their best disposal.

Paper and cardboard:

In waste management, the recycling of paper and cardboard plays an important role, because up to 70% can be reclaimed. The disposal of paper and cardboard can be done through various channels such as collection by private operators or delivery to waste treatment plants.

Plastic:

The recycling of plastics has many advantages for the environment and therefore benefits the quality of life of everyone, contributing to a greater saving of raw materials as well as natural, energy producing and economic resources. The disposal of plastic can be done by private operators or delivered to waste treatment plants.

Bubble wrap:

This is made of low density poly-ethylene, which makes it 100 % recyclable. For optimal disposal, please deliver any waste comprising this material to plastic waste treatment plants.

Our commitment to the environment

One of **Saxun's** objectives is to maintain socially responsible behaviour. This commitment to the environment implies continuous improvements in the measures that are adopted to combat climate change.

Promoting responsible care of the environment, complying with the legal and regulatory requirements applicable to our products and promoting energy saving in all our projects are measures that are essential for us to achieve our objectives.

Disassembly and removal of the product

When disassembling this product, a number of precautionary measures must be taken. Observe the following warnings and instructions. Please contact your supplier with any queries.

Disassembly may only be carried out by experienced fitters. This manual is not intended for DIY enthusiasts or installers in training.

For more information on these disassembly instructions, please refer to the chapters regarding installation in this manual that contain diagrams and detailed information.

Warning

Always act with care. Use appropriate tools which are in perfect condition.

• Étape 1

Disconnect the electricity. ¡ATTENTION! Shut off the energy supply before disconnecting any cables.

• Étape 2

Unscrew the screw on the top cover of the column and remove the cover.

• Étape 3

To remove the side cover, unscrew the right-hand clipping piece and open the left-hand clipping of the rubber bands from the top.

• Étape 4

Dismantle the motor.

• Étape 5

Dismantle the transmission plate.

• Étape 6

Dismantle the slats.

• Étape 7

Dismantle the drainage channels.

• Étape 8

Dismantle the rubber parts.

• Étape 9

Dismantle the pergola structure by disassembling the interior brackets that fasten the beams to the columns, and the wall fixtures, if there are any.

• Étape 10

Dismantle the columns and their fixtures.

Attention

Make sure that you dispose of all the product's parts according to the nature of the material.

Components	Galvanised Steel	Stainless Steel	Aluminium	WEEE	Plastic	Textile
Cables and LED lines				•		
Caps					•	
Switchboard				•	•	
Brackets		•				
Upper brackets		•				
Rubber seal					•	
Motor		•		•	•	
Profile			•			
Motor brackets		•				
End plates			•			
Screws		•				

Our products are mainly made of recyclable materials. It is advisable to be informed about the recycling or disposal systems provided for in the current regulations in your country for this product category.

Important

Always act with care. Please only use suitable tools that are in perfect condition.



This symbol means that the product must not be disposed of together with household waste as it must be collected separately for recovery, reuse or recycling in accordance with local regulations.



In compliance with European Directive 2012/19/EU, waste electrical and electronic equipment (WEEE) can become a serious environmental problem if not managed properly. The Directive provides the general framework valid throughout the European Union for the disposal and re-use of waste electrical and electronic equipment.

At the end of the service life of the electrical or electronic equipment, it must not be thrown away together with other types of waste. They can be delivered to the specific centres regulated for this purpose by the local authorities.

The effective separation of waste will avoid negative consequences for the environment and health that could result from poor waste management or inadequate waste disposal.

Important

By complying with this directive, you will be acting in favour of the environment and will contribute to the conservation of natural resources and the protection of health.

Local regulations may impose significant penalties for illegal disposal of the product.

The materials that our products are made of offer a great variety of environmental advantages



Galvanised steel

Galvanised steel is a type of steel which undergoes a certain treatment, at the end of which it is coated with several layers of zinc which protect it, avoiding oxidation. The recycling of zinc helps reduce demand for new materials and as a result generates considerable energy savings, being a metal that constitutes a very valuable and sustainable resource.

For proper recycling of galvanised steel, it is advisable to visit a metal waste collection centre.



Stainless steel

Stainless steel is an iron alloy containing nickel and chromium to protect against corrosion and rust. Its qualities include resistance to high temperatures and being a particularly strong material. Stainless steel is an infinitely recyclable "green material". Its properties make it ideal for exposure to poor weather conditions.

Therefore, to ensure proper disposal of stainless steel, it is recommended that this material be left at a specialised waste collection centre.



Aluminium

Aluminium recycling guarantees an endless variety of environmental benefits. The use of recycle aluminium saves 95% of the energy used in its production in its raw state, and it can be recycled as many times as desired and is fully recoverable. Therefore, the recycling of aluminium is both technically and economically profitable.

Therefore, to ensure proper disposal of aluminium, it is recommended that this material be left at a specialised waste collection centre.



Cables

The recycling of electrical cables prevents the contamination that can come from these elements. Its re-cycling allows for the subsequent use of the copper, aluminium and brass from the cables, once they are separated from their plastic insulation.

Electrical and electronic waste must be taken to clean points for proper recycling



PET



HDPE



PVC



LDPE



PP



PS



Other

Plastic

Plastic recycling provides a sustainable source of raw material for the industry. Its reuse also significantly reduces environmental problems, as it is a non-biodegradable material.

Recycling reduces energy consumption and CO2 emissions, thus mitigating pollution and climate change.

There are several types of plastic, so to achieve optimal recycling it is essential to deposit them in clean points where the separation of the different types and their identification will take place.



Textiles

The use of textile waste is essential when we talk about recycling. Reuse of such waste helps to reduce the consumption of water and the gases that are released in the manufacturing process.

In order to encourage the proper disposal of textiles, it is recommended that they be left at a specialised waste centre where the different textile fibres will be separated.

! Important

Follow the recommendations for effective product recycling. Remember that recycling is more than an action; it is the value of accepting responsibility

Annex III

Certificate of guarantee

The Saxun bioclimatic pergola is composed of a waterproof structure with adjustable aluminium slats, driven by a motor.

Its main structure is made of 6063 T5 alloy aluminium profiles, lacquered or anodised according to the technical specifications of the Qualicoat and Qualanod quality brands. This structure is totally self-supporting and can be dismantled, so that no type of work or construction is required for its installation.

Our pergolas, just like the rest of our products, are subjected to a variety of tests in our labs in order to check their resistance and behaviour in every type of circumstance.

Tests carried out following the requirements of international standards, involving parameters such as wind resistance and loads of rain or snow, demonstrate the excellent performance of our bioclimatic pergolas against the most adverse conditions.

The P-150 and P-190 pergolas were tested in accordance with the following standards, obtaining the following results;

Wind resistance:

P-150 et P-190	Norme: EN 13659	Class 6 (Aprox. 112 km/h) Tested up to 190 km/h, without breakage due to limitation of the test bench.
-----------------------	------------------------	--

Rain load:

P-150 y P-190	Norme: EN 12056-3	Class: (0.03 l/s max.) torrential rain approx. 108 l.m2/h (structure + slat)
----------------------	--------------------------	---

Snow load:

P-150	Norme: EN 1999 Eurocode 9 Aluminium structures projects.	≤65 kg/m² (Including own weight)
P-190	Norme: EN 1999 Eurocode 9 Aluminium structures projects.	≤100 kg/m² (Including own weight)

Maximum dimensions:

P-150	5.000 mm x 3.600 mm x 3.000 mm*	Approximate weight of 310 Kg
P-190	6.200 mm x 4.200 mm x 3.000 mm*	Approximate weight of 485 Kg

* Length (mm) X Width (mm) X Height (mm)

Warranty:

Saxun only guarantees these results in cases where the pergola has been correctly installed and assembled and properly maintained.

It may be possible for leaks to occur between the slats in the event of occasional heavy rainfall, as the sealing between the slats is not watertight.

The values stated in the calculations shall not be applicable if customers and/or installers not authorised by Saxun manipulate the equipment in any way.

The warranty period for Saxun pergolas is 3 calendar years from the date that the product is supplied, with the date being that indicated in the delivery note issued by GIMÉNEZ GANGA, S.L.U.

For more information about the Saxun warranty conditions and possible exclusions from the warranty, the Saxun Warranty Certificate is available in the general price list.

Client:	Order/Quote:
----------------	---------------------

Prior to placement of columns **OK**

	Squaring and parallel alignment of bases for anchoring to floor slab	
	Strength of attachment of bases for anchoring to floor slab	
	Accurate levelling of bases for anchoring to floor slab	

Prior to installation of slats **OK**

	Strength of wall fasteners	
	Confirm accurate plumbing of columns	
	Confirm accurate levelling of beams	

Prior to final installation of motor **OK**

	Confirm wires are correctly earthed in compliance with REBT	
	Visual inspection of electrical installation, loose cables, pipes, stuffing boxes, closing and sealing of boxes (motor cable)	
	Confirm correct insertion of all security screws (attachment of slat axes)	
	Confirm correct clipping of collectors and slat axes	
	Confirm correct functioning, (smooth and silent) when opening and closing manually, (before installing the motor)	
	Confirm proper sealing by applying water to critical points with a hose or bucket	
	Check tightness of all screws according to tightening chart, (except the transmission)	

During final installation of motor **OK**

	Confirm correct operation of all motor manoeuvres, according to the issuer	
	Re-check and confirm that the drainage collectors, channels and conduits are clean and free of anything that might hinder proper drainage	
	Check profiles and slats are clean (use pH-neutral soap and dilute heavily)	

Check functioning of optional extras **OK**

	LED lighting at all levels	
	Music, Bluetooth and loudspeaker equipment	
	Infra-red heating	
	Rain sensor	
	Temperature sensor	

Warnings

- The structural stability of the pergola cannot be guaranteed if any foreign parts are attached to it.
- The proper evacuation of rainwater cannot be guaranteed if you fail to enable the channels and downspouts recommended in the quotation.

Installer comments	
Date, signature and stamp of installer	<p>I confirm receipt of the installed pergola, with no observable defects. I have received and understood the instructions for use and maintenance, and the warranty conditions.</p> <p>Signed by the client</p>



saxun
by Giménez Ganga

Giménez Ganga, S.L.U.
Polígono Industrial El Castillo
C/ Roma, 4 • 03630
Sax (Alicante) • España

saxun.com